



SUMMER, SIRÉN OCH KOMBISIGNAL KLH (KDH)

710100005

KLH Summer/Sirén med trätt 92 dB 24 V DC

- Membransummer
- 92 dB
- -25°C / +50°C
- IP43 & NEMA type 2
- Steady tone



PRODUKTBESKRIVNING

Liten membransummer till låg kostnad för inomhusbruk.

Finns även i fler spänningsutföranden mot förfrågan.

TEKNISK DATA

Antal toner	1 st
Färg hus	Grå RAL 7035
IP-klass	IP43, NEMA Type 2
Kabelingång	Baksidan
Ljudnivå max	92 dB
Ljudnivå min	92 dB
Matningsspänning	24 V
Matningsspänning DC max	26,4 V DC
Matningsspänning DC min	21,6 V DC
Montering	Vertikal
Nominell ström max	0,026 A
Nominell ström min	0,026 A
Plintanslutning	2,5 mm ²

Temperaturområde från	-25 °C
Temperaturområde till	50 °C
Tonfrekvens max	50 Hz
Tonfrekvens min	50 Hz
Vikt	180 g

The sound pressure decreases by 6 dB when doubling the distance: the following distance table is to be seen as indication, as also factors like tone type, wind speed, wind direction, humidity, weather conditions etc. do influence the sound pressure level.

Distance (m)	Sound pressure dB (A)																					
1	65	70	75	80	85	90	92	94	96	98	100	102	104	106	108	110	112	114	116	118	120	
2	59	64	69	74	79	84	86	88	90	92	94	96	98	100	102	104	106	108	110	112	114	
3	55	60	65	70	75	80	82	84	86	88	90	92	94	96	98	100	102	104	106	108	110	
5	51	56	61	66	71	76	78	80	82	84	86	88	90	92	94	96	98	100	102	104	106	
10	45	50	55	60	65	70	72	74	76	78	80	82	84	86	88	90	92	94	96	98	100	
20	39	44	49	54	59	64	66	68	70	72	74	76	78	80	82	84	86	88	90	92	94	
30	35	40	45	50	55	60	62	64	66	68	70	72	74	76	78	80	82	84	86	88	90	
50	36	41	46	51	56	60	62	64	66	68	70	72	74	76	78	80	82	84	86	88	90	
100				40	45	50	52	54	56	58	60	62	64	66	68	70	72	74	76	78	80	
200				39	44	46	48	50	52	54	56	58	60	62	64	66	68	70	72	74	76	
500				38	40	42	44	46	48	50	52	54	56	58	60	62	64	66	68	70	72	

The sound pressure decreases by 6 dB when doubling the distance.

The sound pressure decreases by 6 dB when doubling the distance

