

ADAPTERS PLAST

10063628

Adapter polyamid M12-PG7 Grå



PRODUKTBESKRIVNING

Teknisk data

Temperaturområde	-40 till +100 °C
Material	Polyamid
Godkännanden	

AMP Form A		AMP Form B						
Best.nr. RAL 7035	Typ	Da	Di	Nyckel vidd (SW)	Gänga längd	Total längd (TL)	Form	Förp.- storlek
10063628	AMP 12/7	M 12X1,5	PG 7	16	9	27	A	25
10063629	AMP 12/9	M 12X1,5	PG 9	20	9	27	A	25
10063630	AMP 16/9	M 16X1,5	PG 9	20	9	27	A	25
10063631	AMP 16/11	M 16X1,5	PG 11	22	9	27	A	25
10063632	AMP 16/13,5	M 16X1,5	PG 13,5	24	9	27	A	25
10063633	AMP 20/11	M 20X1,5	PG 11	24	9	27	A	25
10063634	AMP 20/13,5	M 20X1,5	PG 13,5	24	9	27	A	25
10063635	AMP 20/16	M 20X1,5	PG 16	27	9	27	A	25
10063636	AMP 25/13,5	M 25X1,5	PG 13,5	24	10	17	B	25
10063637	AMP 25/16	M 25X1,5	PG 16	29	10	28	A	25

10063638	AMP 25/21	M 25X1,5	PG 21	33	10	28	A	25
10063639	AMP 32/16	M 32X1,5	PG 16	36	12	19	B	10
10063640	AMP 32/21	M 32X1,5	PG 21	36	12	30	A	10
10063641	AMP 32/29	M 32X1,5	PG 29	42	12	30	A	10
10063642	AMP 40/21	M 40X1,5	PG 21	46	12	19	B	10
10063643	AMP 40/29	M 40X1,5	PG 29	46	12	30	A	10
10063644	AMP 40/36	M 40X1,5	PG 36	53	12	30	A	10
10063645	AMP 50/36	M 50X1,5	PG 36	55	14	32	A	5
10063646	AMP 50/42	M 50X1,5	PG 42	60	14	42	A	5
10063647	AMP 50/48	M 50X1,5	PG 48	65	14	32	A	5
10063648	AMP 63/42	M 63X1,5	PG 42	68	15	22	B	5
10063649	AMP 63/48	M 63X1,5	PG 48	68	15	33	A	5

Rekommenderade tillbehör



EMUG



EADR

PG-METRISK

Teknisk data

Temperaturområde	-40 till +100 °C
Material	Polyamid
Godkännanden	

APM Form A		APM Form B						
Best.nr. RAL 7035	Typ	Da	Di	Nyckel vidd (SW)	Gänga längd	Total längd (TL)	Form	Förp.- storlek
10063650	APM 7/12	PG 7	M 12X1,5	16	9	27	A	25
10063651	APM 7/16	PG 7	M 16X1,5	20	9	27	A	25
10063652	APM 9/12	PG 9	M 12X1,5	20	9	27	A	25
10063653	APM 9/16	PG 9	M 16X1,5	20	9	27	A	25
10063654	APM 9/20	PG 9	M 20X1,5	24	9	27	A	25

10063655	APM 11/16	PG 11	M 16X1,5	22	9	27	A	25
10063656	APM 11/20	PG 11	M 20X1,5	24	9	27	A	25
10063657	APM 11/25	PG 11	M 25X1,5	29	9	27	A	25
10063658	APM 13,5/16	PG 13,5	M 16X1,5	24	10	28	A	25
10063659	APM 13,5/20	PG 13,5	M 20X1,5	24	10	28	A	25
10063660	APM 13,5/25	PG 13,5	M 25X1,5	29	10	28	A	25
10063661	APM 16/20	PG 16	M 20X1,5	27	10	28	A	25
10063662	APM 16/25	PG 16	M 25X1,5	29	10	28	A	25
10063663	APM 16/32	PG 16	M 32X1,5	36	10	28	A	25
10063664	APM 21/25	PG 21	M 25X1,5	33	12	30	A	10
10063665	APM 21/32	PG 21	M 32X1,5	36	12	30	A	10
10063666	APM 21/40	PG 21	M 40X1,5	46	12	30	A	10
10063667	APM 29/32	PG 29	M 32X1,5	42	12	19	B	10
10063668	APM 29/40	PG 29	M 40X1,5	46	12	30	A	10
10063669	APM 29/50	PG 29	M 50X1,5	55	12	30	A	10
10063670	APM 36/40	PG 36	M 40X1,5	53	14	21	B	10
10063671	APM 36/50	PG 36	M 50X1,5	55	14	32	A	10
10063672	APM 36/63	PG 36	M 63X1,5	68	14	32	A	5
10063673	APM 42/40	PG 42	M 40X1,5	60	14	21	B	5
10063674	APM 42/50	PG 42	M 50X1,5	60	14	32	A	5
10063675	APM 42/63	PG 42	M 63X1,5	68	14	32	A	5
10063676	APM 48/50	PG 48	M 50X1,5	65	15	22	B	5
10063677	APM 48/63	PG 48	M 63X1,5	68	15	33	A	5

Rekommenderade tillbehör



MUG



ADR

TEKNISK DATA

Dimension Da	M12x1,5
Dimension Di	PG7

Färg	Grå RAL 7035
Förpackningsstorlek	25 st
Godkännanden	RoHS
Gänglängd	9 mm
Längd total	27 mm
Material	Polyamid
Nyckelvidd	16 mm
Temperaturområde från	-40 °C
Temperaturområde till	100 °C

