



Material:

- Housing: Zinc die-cast, chrome plated or black texture powder coated.
- Cylinder: Zinc die-cast, stainless steel cap and dust shutter.
- Nut: Zinc die-cast, zinc plated.
- Screw and cam: Steel, zinc plated.

References, Accessories:

- Cams with projection: 2-480 and 2-490 - cam rotates 90° and the key can be removed in the locked position.
- Cams without projection: 2-481 and 2-491 - cam rotates 180° and the key can be removed in both open and locked position.

Notes, Tests:

Master key system (marked with *) is supplied on request only.

Quarter-turn cylinder lock. Universal clockwise or counter-clockwise rotation when opening / closing. Supplied with nut. Protection degree IP54. Supplied with two keys.

Cylinder Lock - 56,5 mm (AAAAA-BBB-HHLL)

AAAAA-	Surface treatment	Cylinder	Nut	BBB	Cam rotation	-HHLL	Cam size in mm
241356-	Chrome	Keyed alike, IL 101	Standard	180	180°	-0000	No cam
241556-	Black	Keyed alike, IL 101	Standard	090	90°	-HH45	See cam ref. above.
241358-	Chrome	Keyed alike, IL 101	Earthing nut				H between 42-88 mm in increments of 2 mm
241558-	Black	Keyed alike, IL 101	Earthing nut				
241357-	Chrome	Keyed to differ	Standard				
241557-	Black	Keyed to differ	Standard				
241359-	Chrome	Keyed to differ	Earthing nut				
241559-	Black	Keyed to differ	Earthing nut				
241357-HNS *	Chrome	Master key system	Standard				
241557-HNS *	Black	Master key system	Standard				