



Identification	Type Part-No.	LCIS-WAA-0901-62-S 750901.0000
Description	Output: 0–60 mV Output: 0–10 V / 0–20 mA / 4–20 mA Insulation: 2.5 kV, 3-way isolation	
Input	Input variable Voltage 0-60 mV Galvanic isolation I/O 3-way isolation Measuring procedure Voltage measurement Parameterisation DIP switch S1 Zero /Span Production comparison Input resistance >1 MΩ Protection device Overvoltage protection	
Output	Output signal 0–10 V, 0–20 mA, 4–20 mA Max. load impedance at I-output 500 Ω Min. load impedance at U-output 2 kΩ Load deviation at U-output max. 5 mV @ 2 kΩ Output voltage < 16 V @ 0–20 mA, 4–20 mA	

20.10.2017 – Subject to technical modification

Part-No. 750901.0000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet • Interface Technology

Output current	max. 5 mA @ 10 V
Residual ripple	<20 mV _{eff}
Parameterisation	DIP switch S1
Protection device	short circuit protection

Operating data

Accuracy	0.1 % FSR @ 23 °C
Linearity error	0.1 % FSR
Rise time (10 - 90%)	approx. 30 ms @ 23 °C
Build-up time (Accuracy 1%)	approx. 60 ms @ 23 °C
Temperature coefficient	150 ppm / K FSR
Critical frequency	10 Hz @ 3 dB / 23 °C

General

Rated voltage	AC/DC 24 V
Operation voltage range	AC 19.2–26.4 V / DC 18.0–31.2 V
Rated current	approx. 22 mA @ AC 24 V / approx. 13 mA @ DC 24 V
Status indication	LED green
Rise time (10 - 90%)	approx. 30 ms @ 23 °C
Insulation voltage input / output	2.5 kV _{eff}
Housing material	PA 6.6 (UL 94 V-0, NFF I2, F2)
Color of the housing	RAL 7012 basalt grey
Mounting	DIN rail mountable TS35 (EN 60715)
Protection class	IP20
Installation position	any
Connection device	Screwed terminal single wire 0.25 mm ² –2.5 mm ² / AWG 20–14 fine stranded wire with ferrule 0.25 mm ² –1.5 mm ² / AWG 20–16
Operation temperature range	-25 °C ... +60 °C
Storage temperature range	-40 °C ... +85 °C
Dimensions (w × h × d)	6.2 × 93.0 × 73.0 mm
Weight	0.030 kg/piece
PU	1 piece
Approvals	cULus in preparation DNV GL in preparation
Standards	EN 60947-5-1

20.10.2017 – Subject to technical modification

Part-No. 750901.0000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU


Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk




SYSTEMATIC TECHNOLOGY

Dimensions



PIN assignment



Range adjustment

S1	Output
• → Switch On	5/6
0–10V	•
0–20mA	•
4–20mA	•

S1	Input
• → Switch On	1/2/3/4
0–60 mV	

20.10.2017 – Subject to technical modification

Part-No. 750901.0000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY