



Identification	Type Part-No.	LCIS-WP-WPT3LA-0817-175-S 750817.0000
Description	Input: PT100, 2-wire/3-wire Output: 0–10 V / 0–20 mA / 4–20 mA Insulation: 4.0 kV, 3-way isolation	
Input	Input variable Temperature sensor PT100 Galvanic isolation I/O 3-way isolation Measuring procedure 2-wire of 3-wire, constant current Temperature range -50 °C–50 °C / -50 °C–100 °C / -50 °C–150 °C / 0 °C–100 °C / 0 °C–150 °C / 0 °C–200 °C / 0 °C–300 °C / 0 °C–400 °C Parameterisation DIP switch S1 Zero /Span Production comparison Input resistance >1 MΩ @ 2-wire, >500 kΩ @ 3-wire Sensor current 0.5 mA Protection device Input Overvoltage protection	
Output	Output signal 0–10 V, 0–20 mA, 4–20 mA Max. load impedance at I-output 500 Ω Min. load impedance at U-output 2 kΩ	

16.08.2019 – Subject to technical modification

Part-No. 750817.0000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · Interface Technology

Load deviation	at U-output max. 5 mV @ 2 k Ω
Output voltage	< 18 V @ 0–20 mA, 4–20 mA
Output current	max. 5 mA @ 10 V
Residual ripple	<20 mV _{eff}
Parameterisation	DIP switch S1
Protection device	short circuit protection

Operating data

Accuracy	0.3 % FSR @ 23 °C
Linearity error	0.1 % FSR
Rise time (10 - 90%)	approx. 30 ms @ 23 °C
Build-up time (Accuracy 1%)	approx. 60 ms @ 23 °C
Temperature coefficient	150 ppm / K FSR
Critical frequency	10 Hz @ 3 dB / 23 °C
Error coefficient of measuring line	2-conductor: 2.7 K/ Ω , 3-conductor: 0.1 K + 0.1 %/ Ω

General

Rated voltage U _N	AC/DC 24–240 V
Operation voltage range	AC 19.2–264 V / DC 18.0–264 V
Rated current	appr. 22 mA @ AC 24 V / appr. 19 mA @ DC 24 V
Status indication	LED green
Rise time (10 - 90%)	approx. 30 ms @ 23 °C
Insulation voltage input / output	4.0 kV _{eff}
Housing material	PA 6.6 (UL 94 V-0, NFF I2, F2)
Color of the housing	RAL 7012 basalt grey
Mounting	DIN rail mountable TS35 (EN 60715)
Protection class	IP20
Installation position	any
Connection type	Screwed terminal single wire 0.25 mm ² –2.5 mm ² / AWG 20–14 fine stranded wire with ferrule 0.25 mm ² –1.5 mm ² / AWG 20–16
Operation temperature range	–25 °C ... +60 °C
Storage temperature range	–40 °C ... +85 °C
Dimensions (w × h × d)	17.5 × 93.0 × 73.0 mm
Weight	0.059 kg/piece
PU	1 piece
Approvals	cULus in preparation DNV GL
Standards	EN 60947-5-1

16.08.2019 – Subject to technical modification

Part-No. 750817.0000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · Interface Technology

Failure Rate Prediction (MTBF)

Standards

Electronic components – Reliability – Reference conditions for failure rates and stress models for conversion: EN/IEC 61709

Failure Rates of Components – Expected values: SN 29500

Failure rate at +45 °C

713 fit

Failure rate at +45 °C

1402367 h

1 fit equals one failure per 10⁹ component hours

The indicated temperature is the mean component ambient temperature.


Comments

The results are valid under following conditions:


Automotive environment or industrial areas without extreme dust levels and harmful substances

Continuous operation 8760 h per year

Dimensions



PIN assignment



16.08.2019 – Subject to technical modification

Part-No. 750817.0000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · Interface Technology

Range adjustment

S1	Output
• → Switch On	5 6
0–10V	●
0–20mA	●
4–20mA	●●

S1	Input
• → Switch On	1 2 3 4
PT100, 3-wire	
PT100, 2-wire	●
-50 – 50°C	
-50 – 100°C	●
-50 – 150°C	●
0 – 100°C	●●
0 – 150°C	●●
0 – 200°C	●●
0 – 300°C	●●
0 – 400°C	●●

16.08.2019 – Subject to technical modification

Part-No. 750817.0000

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY