


ENSTO

KE33

Radklämma

Kod	KE33
GTIN	6418677161704
E-nummer	2673511
Namn	Radklämma Ensto Clampo Compact Grå, Cu 1,5-35 mm ² , 750 V
Beskrivning	Ensto Clampo Compact-kompaktradklämmor är idealiska att använda när utrymmet är begränsat. Det kompakta utförandet gör att kompaktradklämmorna kan installeras snabbt, antingen direkt på en underlag eller på en DIN 15- eller DIN 35-skena.
Återförsäljare	Ensto Finland Oy

**Teknisk specifikation****Dimensioner**

Vikt:	0.04 kg
Ledartvärsnitt:	35
Volym :	3.08 cm ³

Temperaturer

Drifttemperatur:	≤ 80 °C
------------------	---------

Elektriska värden

Nominell isolationsspänning:	750 V
Nominell ström A:	135 A

Material

Kåpa:	Polyamid
-------	----------

Färg

Färg:	Grå
-------	-----

Egenskaper

Skruvskalle: Spårskalle

Fastsättning: DIN-skena

Mekanisk

Åtdragningsmoment: 3.5 Nm

Certifikat

Standarder: EN 60947-7-1, EN 60998-1, UL 1059

UL-kategori: XCFR2

UL filnummer: E192532, E192532

Betyg

ETIM 7: EC000897

US specific

Ledarstorlek: 2-16

Max. spänning: 600 V

Åtdragningsmoment: 40.5 Lb-In

Maxström: 115 A

ETIM

ETIM

Length: 50 mm

Material insulation body: Thermoplastic

Rated voltage: 750 V

Width/grid dimension: 14 mm

Mounting method: DIN rail (top hat rail) 35 mm

Colour: Grey

Type of electrical connection 1: Screw connection

Number of levels: 1

Height at lowest possible mounting height: 44 mm

Operation temperature: -5 ... 80 °C

Connectable conductor cross section fine-strand with cable end sleeve: 1.5 ... 25 mm²

Number of clamp positions per level: 2

Connectable conductor cross section fine-strand without cable end sleeve: 1.5 ... 25 mm²

Explosion-tested version 'Ex e': false

Connectable conductor cross section multi-wired: 1.5 ... 35 mm²

Inflammability class of insulation material acc. with UL94: V2

Rated current I_n: 135 A

Type of electrical connection 2: Screw connection

Connection position: Sideways

Förpackning

Förpackning

Unit:	PCS
Size:	100
Length:	220 mm
Width:	220 mm
Height:	175 mm
Weight (brt):	4.3814 kg
Volume:	8.47

Pallet package

Unit:	PCS
Size:	7500
Length:	1200 mm
Width:	800 mm
Height:	1025 mm
Weight (brt):	353.6 kg
Volume:	984