



General information

The most significant advantage and potential of the PLTC label is its continuous form, which enables to design and print labels of any length. Available in different height.

Vinyl label is characterized by high adhesion and is a perfect solution for rough surfaces and no straight shapes.

Durable acrylic adhesive allows using the tape on many surfaces, including stainless steel and glass.

UV resistance material.

PLTC label tape


- Tape, permanent or removable
- Print with thermal transfer printer
- · Perfect for component marking

A soft and flexible universal tape, for indoor and outdoor use. Excellent resistance to moisture, alcohols and oil.


Print the continous tape in requested length via a thermal transfer printer and Partex software Promark Creator.

Technical information





Min application temperature: +2°C



• Adhesive: permanent Acrylic adhesive

• Expiry date: 24 month at+21°C and 50% RH.

Article No	Description	Height mm	Color	Packaging m/reel
PLTC009000D*V^	PLTC tape	9	yellow, white	100
PLTC012000D*VP	PLTC tape	12	yellow, white	100
PLTC025000D*VP	PLTC tape	25	yellow, white	60
PLTC050000D*VP	PLTC tape	50	yellow, white	30
PLTC100000D*VP	PLTC tape	100	yellow, white	30

^{*} Color. Yellow=4. White=9 (standard colors)

[^]Tape. P=Permanent tape, R=Removable tape